

# Line 6 Amp Farm v3.0 Plug-In

Thank you for purchasing Amp Farm v3.0 for ProTools|HD Accel and Pro Tools|HD systems. Amp Farm v3.0 supports Windows XP and Mac OS X systems.

---

## What's New in Amp Farm v3.0

- New Speaker Cabinet models based on technology from the acclaimed Line 6 PODxt series hardware
- New Mic models based on technology from the acclaimed Line 6 PODxt series hardware
- Support for Pro Tools 6.7 and D-Show

---

## Amp Farm Plug-In Guide

The *Amp Farm Plug-In Guide* is a PDF file. It is the primary source of information on features, capabilities, and operational recommendations for Amp Farm.


---

## Authorizing the Amp Farm Plug-In

Amp Farm is authorized using the iLok USB Smart Key and License Card from PACE Anti-Piracy.

The iLok is similar to a dongle, but unlike a dongle, it is designed to securely authorize multiple software applications from a variety of software developers.

This key can hold over 100 authorizations for all of your iLok-enabled software. Once an iLok is authorized for a given piece of software, you can use the iLok to authorize that software on any computer.

 *The iLok USB Smart Key is not supplied with your plug-in. You can use the one included with your Pro Tools|HD Core system, or purchase one separately.*

*If you are a ProTools|24 MIX user and do not own an iLok key, you can purchase one from a Digidesign Dealer or the online Digi Store.*

License Cards are specific to each plug-in. You will receive the appropriate License Cards for the plug-ins that you purchase. License Cards have a small punch-out plastic chip called a GSM cutout.

 *For additional information about iLok technology and authorizations, see the electronic PDF of the iLok Usage Guide.*

### To authorize Amp Farm with iLok:

- 1 Insert the iLok into an available USB port on your computer.
- 2 Launch Pro Tools. You will be prompted to authorize any installed unauthorized plug-ins or software options.

 *If you are already using a demo version of the plug-in, launch Pro Tools before you insert the iLok, then insert the iLok into any available USB port when prompted by Pro Tools.*

- 3 Follow the on-screen instructions until you are prompted to insert the License Card into the iLok.

- 4 Separate the GSM cutout from the larger protective card by pulling it up and out with your thumb. Do not force the cutout down with your finger.
- 5 Insert the GSM cutout into the iLok. Visually verify that the metal portion of the cutout makes contact with the iLok's metal card reader.



*iLok with License Card GSM cutout inserted*

- 6 Follow the on-screen instructions to complete the authorization process.
- 7 After the authorization has completed, remove the GSM cutout from the iLok. (If you have to remove the iLok from the computer to remove the cutout, be sure to re-insert the iLok in any available USB port on your computer when you are finished.)

---

## **Known Issues**

### **Amp Farm 2.x Preset Compatibility**

Factory and custom presets created for Amp Farm 2.x will work within Amp Farm 3.x. However, if changes are made to these presets with Amp Farm 3, you will need to save them so that they can be recalled with the session. Additionally, note that presets created in Amp Farm 3.x are not compatible with Amp Farm 2.